

INDOOR

LOW SHOE

LOW SHOES

S1P

SRC

HRO

The +

- Sporty design
- Lightweight
- Flexible
- Breathable

0%
METAL

PURCHASE PACKAGING

REF.	EU	US	
9FLU160038	38	5.5	10
9FLU160039	39	6	10
9FLU160040	40	7	10
9FLU160041	41	8	10
9FLU160042	42	8.5	10
9FLU160043	43	9.5	10
9FLU160044	44	10	10
9FLU160045	45	11	10
9FLU160046	46	11.5	10
9FLU160047	47	12.5	10

DESCRIPTION

FLUORITE is a low safety shoe inspired by the running universe. Its upper made of polyester mesh and KPU (Thermoplastic polyurethane) provides great breathability and improved durability. The Polyester mesh lining offers comfort of use, just as its insole in textile and EVA with holes. The EVA/rubber outsole offers excellent cushioning, durability and grip.

FLUORITE is metal free. It features a composite toe-cap and an anti-penetration plate made of textile which ensure both protection and flexibility. This shoe is ideal for work environments such as logistics, construction finishing works or DIY.

SECTORS

Service

Second work

Handyman

Transport ang logistics

APPLICATIONS EXAMPLES

- Painter,
- Electrician,
- Storekeeper, ...

TECHNICAL FEATURES

Closure	Lacing	Anti perforation sole	Textile
Toe cap	Composite	Reinforced part of shoe	KPU reinforcements on the upper
Work environment	Indoor	Examples of applications	Painter, Electrician, Storekeeper, ...
Sub-family	Low shoe	Color	Green/Grey
Upper	Mesh with KPU (thermoplastic polyurethane) upper	Insole	Removable, perforated EVA
Loops	Textile loops	Midsole	EVA
Wearing sole	Nitrile rubber	Main assembly	Cemented assembly
Lining	Breathable 3D mesh		

INSTRUCTIONS FOR USE AND STORAGE**Instructions for use :**

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes.

LEGISLATION

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate **2777/13373-01/E00-00**.
Delivered by **SATRA (2777)**.

EN ISO 20345:2011

S1P SRC HRO

S1P : Closed heel, antistatic shoe, fuel and oil resistant contact outsole, energy absorbing heel, puncture resistant midsole, resistant to a 1 100 Newtons pressure

SRC : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

HRO : Heat contact resistant outsole (60 seconds at 300°C)

PPE CAT. II

Major risks

Retailer stamp