

Ref. 9SCHH10

Multipurpose

High

High shoes



The +

- * Sport design
- * Free metal
- * Reflective trim
- * Defined and raised heel

PURCHASE PACKAGING

| Référence | Taille | Carton |
|------------|--------|--------|
| 9SCHH10038 | | 6 |
| 9SCHH10039 | 39 | 6 |
| 9SCHH10040 | 40 | 6 |
| 9SCHH10041 | 41 | 6 |
| 9SCHH10042 | 42 | 6 |
| 9SCHH10043 | 43 | 6 |
| 9SCHH10044 | 44 | 6 |
| 9SCHH10045 | 45 | 6 |
| 9SCHH10046 | 46 | 6 |
| 9SCHH10047 | 47 | 6 |

DESCRIPTION

SCHORL is a low safety shoe inspired by the trail universe. Its upper made of Oxford polyester provides breathability and durability. The front, sides and back reinforcements in KPU increase long lastingness and is suitable to users working squatting or kneeling. Reflective stripes improve safety of people working at night. Metal free, this shoe features a composite toe-cap and a textile anti-penetration sole that bring better flexibility and better thermal insulation than steel shoes. The nitrile rubber clitted outsole and polyurethane midsole combine the advantages of both materials: comfort and resistance. SCHORL suits the requirements of standard indoor and outdoor uses.

SECTORS

Light Industries

Construction - finishing work

DIY

Transport (excluding manufacturing) and logistics

Services and distribution

TECHNICAL FEATURES

| | |
|--------------------------------|---------------------------|
| Color | Black |
| Upper | Mesh |
| Toecap | Composite |
| Puncture resistant sole | Textile |
| Midsole | PU |
| Outsole | Rubber nitrile |
| Insole | Removable, perforated EVA |
| Closing | Lacing closure |
| Lining | Breathable 3D mesh |

INSTRUCTION FOR USE AND STORAGE

Instructions for use

These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

Storage instructions

Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

Washing instructions

Regularly clean the shoes by using brushes, cleaning clothes.

STANDARD(S)



EN ISO 20345:2011

S3

SRC

EPI CAT. I

Safety shoes

S3 Basic requirements: a 200 Joule impact and 15 000 Newton compression resistant toe-cap + Closed heel + Antistatic shoe $0,1M\Omega < A < 1000 M\Omega$ + Fuel and oil resistant contact outsole + Energy absorbing heel $E \geq 20$ Joules + Puncture resistant midsole / Resistant to a 1 100 Newtons pressure + Water penetration and absorption resistant upper + Spiked outsole + Puncture resistant midsole

Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

RETAILER STAMP