ALPHA SOTA M2

MEDIUM ATTENUATION EAR DEFENDER



A high performance, comfortable ear defender without the weight, M2 features large, soft ear cushions and a flexible padded headband. The M2 model is fully adjustable to provide a superior fit for most head sizes.

FEATURES

- NR 30dB
- Lower profile cup design
- Large ear cushions allow freedom to fit majority of ears for a comfortable fit
- Easy on head adjustment thanks to individual slide action
- Padded, durable headband provides lasting comfort
- Low pressure but high performance ear defender
- Stylish green and black design
- Quality gloss finish for easy maintenance
- Full integration with other PPE
- Approved to EN352-1: 2002



ORDERING INFORMATION

Part Number: M2

Packaging: 1 Ear Defender per box

20 boxes per case

Certification: EN352-1: 2002

SUITABLE APPLICATIONS

An effective solution for those exposed to very high noise levels. Typical industries include;

- Airfield Operations
- Boiler Rooms
- Bottling Plants
- Compressors
- Craftwork
- Drilling Concrete
- Fabrications
- Food Processing
- Heavy Industry
- Iron Processing
- Mining
- Oil and Gas
- Pneumatic Tools
- Transportation
- Utilities and Highway Maintenance



LPHA SOTA M2



MEDIUM ATTENUATION EAR DEFENDER

TECHNICAL SPECIFICATIONS

ATTENUATION DATA

| Frequency (Hz) | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|-------------------------------|------|------|------|------|------|------|------|
| Mean Attenuation (dB) | 18.4 | 22.5 | 33.4 | 38.8 | 37.0 | 39.6 | 40.4 |
| Standard Deviation (dB) | 3.7 | 2.9 | 2.3 | 2.4 | 2.6 | 3.1 | 2.3 |
| Assumed Protection (dB) | 14.8 | 19.6 | 31.2 | 36.4 | 34.4 | 36.5 | 38.0 |

M2 EAR DEFENDERS SNR = 30dB H = 36dB M = 30dB L = 22dB

MATERIALS

| Component | Material | | | | |
|--------------------|---|--|--|--|--|
| Headband Cushion | Foam covered with PVC cloth and woven cloth | | | | |
| Headband Connector | ABS | | | | |
| Wire | Steel with chrome plated | | | | |
| Clip | ABS | | | | |
| Cup | ABS (with foam inside) | | | | |
| Cup Cushion | Foam covered with PVC cloth | | | | |
| Ring | ABS | | | | |

Assumed Protection rounded to one decimal place

Results of tests performed in accordance with the standard BS EN352-1: 2002.

CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: SATRA Technology Europe Limited, Bracetown Business Park, Clonee D15 YN2P, Republic of Ireland. [N.B. No.2777].

STORAGE & MAINTENANCE

Before use, always keep the ear defender in its original packaging and in a dry, clean, uncontaminated environment. To avoid potential damage, ensure the earpiece pads are not pressed together during storage.

Regularly inspect the ear defender for signs of damage and potential loss of sound attenuation. This product may be cleaned using a damp cloth and mild soapy water but not with chemicals. Allow to dry before use. Do not use abrasive cloths or brushes which may cause damage upon contact with any surface of the product. Further information can be obtained from the manufacturer.

ALPHA-DAIA