

TDM cut level D, food contact approved, washable up to 36 times. Comfortable and very cost effective. OEKO-TEX standard 100.

KEY FEATURES

- Food contact approved, TDM cut level D protection
- · Washable up to 36 times, very durable and cost efficient
- Great dexterity, flexibility & fitting. Comfortable
- · Blue color for easier recognition
- OEKO-TEX standard 100 certified.



















PRODUCT DETAILS

Liner Gauge

UHMWPE mixed with other yarns

10

Coating

N.A.

Finishing

N.A.

Colour

Blue

Size

6,7,8,9,10,11,12

Packing

1 Pair/pack, 12 pairs/polybag, 120 pairs/carton

Tariff number

61169300

RECOMMENDED APPLICATIONS

General purpose, food processing works with cut hazards in dry, wet or oily conditions.

Such as meat processing, fish processing, vegetable and fruit processing and etc.





















Xcellent_® 12-260

CERTIFICATION



EN420:2003 + A1:2009

Category II

EN388:2016 Mechanical protection: levels obtained in laboratory tests

Abrasion (min.0 to max. 4):

Blade cut - coupe test (Index) (min.0 to Max. 5):

Tear (min.0 to max. 4):

Puncture (min.0 to max. 4):

Cut resistance from sharp objects EN ISO

13997:1999 (min. A to Max. F, X - not tested):

Impact protection (P if pass, F if failed):

EN388:2016



D

EN420:2003+A1:2009 Dexterity (min.0 to max.5):

Food Contact Approval Tests, EN1186 results obtained in laboratory tests

| Simulant(s) Used | Test Condition | Result(s) [mg/dm²] | Maximum Permissible Limit [mg/dm²] |
|------------------|-------------------|-----------------------|------------------------------------|
| 3% Acetic Acid | 70°C for 2 hours | 2.25 | 10 |
| 95% Ethanol | 60°C for 2 hours | 1.05 | 10 |
| Iso-octane | 40°C for 0.5 hour | <0.500 | 10 |

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-260 can normally be 5 years.

CLEANING

60 °C water wash in 30 minutes. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.



