



Water and oil repellent, flexible and comfortable. 13 gauge, cut protection level D, sandy nitrile. Reinforced.

KEY FEATURES

- Water and oil repellent, cut protection level D
- Reinforcement greatly extends glove life to save your cost and provides extra protection in the most weakest
- Sandy finish provides super grip in oily and dry working condition
- Flexibility, comfort and good fit, less hand fatigue
- Contact heat protection up to 100 °C according to EN407
- OEKO -TEX standard 100 certified for skin friendly



PRODUCT DETAILS

Liner	UHMWPE mixed with other yarns
Gauge	13
Coating	Nitrile
Finishing	Flat & Sandy
Colour	Grey / Blue & Black
Size	7,8,9,10,11
Packing	6 pairs/pack, 72 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose or works with high cut hazard or contact heat hazard in oily or wet conditions.

Such as oil or fluids or other liquid (not chemicals) change, equipment maintenance, recycling, press shop works, inspection, assembly, sheet metal work, work with sharp or rough edge parts...



CERTIFICATION



EN420:2003 + A1:2009

Category II

EN388:2016 Mechanical protection:
levels obtained in laboratory tests

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to Max. 5): **X**
Tear (min.0 to max. 4): **4**
Puncture (min.0 to max. 4): **4**
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to Max. F, X - not tested): **D**
Impact protection (P if pass, F if failed): **-**

EN388:2016



4X44D

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

EN407:2004 Heat protection:
levels obtained in laboratory tests

A - Burning behaviour: X of 4
B - Contact heat: 1 of 4
C - Convective heat: X of 4
D - Radiant heat: X of 4
E - Small drops molten metal: X of 4
F - Large quantity molten metal: X of 4

EN407:2004



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 12-368 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals or electrical risk.

Please ensure the products are strictly used within their protection levels.

