



Second skin feeling. Extremely light, perfect dexterity and flexibility. 18 gauge, X-wet Polyurethane.

KEY FEATURES

- Second Skin Feeling. Extreme light glove with perfect dexterity, flexibility and minimum hand fatigue
- Special X-wet PU formulation offers better grip performance than similar products in the market
- Super soft, comfortable and perfect fit
- 10-finger touch screen functionality enables you to use all touch screen devices on the jobs
- Much lighter than a standard 13 gauge PU glove
- Individual pack available for retail shops



PRODUCT DETAILS

Liner	Nylon
Gauge	18
Coating	Polyurethane
Finishing	X-Wet
Colour	Blue / Black
Size	6,7,8,9,10,11
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61161080

RECOMMENDED APPLICATIONS

General purpose or precision works in dry conditions.

Such as fine assembly and disassembly, inspection, sorting, handling small parts, general handling, adjusting systems...



CERTIFICATION

CE EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):	3
Blade cut - coupe test (Index) (min.0 to Max. 5):	1
Tear (min.0 to max. 4):	2
Puncture (min.0 to max. 4):	1
Cut resistance from sharp objects EN ISO 13997:1999 (min. A to Max. F, X - not tested):	X
Impact protection (P if pass, F if failed):	-

EN388:2016



3121X

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 18-001 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

