



Superior cut protection sleeve - level F, special design. Very soft and comfortable. 13 gauge.

KEY FEATURES

- Superior cut protection sleeve - cut protection level F
- Special design in the upper arm together with Velcro makes it better fit the arm, comfortable and holds the sleeve in position when wearing
- Advanced yarns wrapping and knitting technology provides super cut protection but also great wearing comfort
- High visibility color offers more safety when working in dark or outdoor conditions



PRODUCT DETAILS

Liner	Steel fiber, UHMWPE, others
Gauge	13
Coating	N.A.
Finishing	N.A.
Colour	Hi-vis Yellow / Black
Length	45 cm
Packing	12 pairs/pack, 144 pairs/carton
Tariff number	61143000

RECOMMENDED APPLICATIONS

General purpose, or works with high cut hazards.

Such as handling sharp edge parts, handling electronics parts, handling metal sheets or panels, cutting and etc.



CERTIFICATION

 EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4):

3

Blade cut - coupe test (Index) (min.0 to Max. 5):

X

Tear (min.0 to max. 4):

4

Puncture (min.0 to max. 4):

X

Cut resistance from sharp objects EN ISO

13997:1999 (min. 0 to Max. F, X - not tested):

F

Impact protection (P if pass, F if failed):

-

EN388:2016



3X4XF

EN420:2003+A1:2009 Dexterity (min.0 to max.5):
level 5.

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general.

The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 30-745Y can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.

Please ensure the products are strictly used within their protection levels.

