




Super abrasion resistance, great grip and additional durability. Improved coating. 360° better breathability.

KEY FEATURES

- High quality nitrile dots contribute to super abrasion resistance, great grip and additional durability
- OEKO-TEX standard 100 certified for skin friendly
- Improved coating contributes to more softness and durability
- Great grip in wet, oily and dry working conditions
- Thanks to different coating processing, it provides better 360° breathability than many other similar products



PRODUCT DETAILS

Liner	Nylon mixed with other yarns
Gauge	15
Coating	Nitrile
Finishing	Sandy Dotted
Colour	Grey / Blue & Grey
Size	6,7,8,9,10,11,12
Packing	2 pairs/pack, 12 pairs/polybag, 120 pairs/carton
Tariff number	61161020

RECOMMENDED APPLICATIONS

General purpose work under dry, little wet/oily working conditions.

Such as assembly and disassembly works, general handling, logistics, maintenance, inspection, sorting, machine operating, screwing, warehouse works...



CERTIFICATION

CE EN420:2003 + A1:2009

Category II

**EN388:2016 Mechanical protection:
levels obtained in laboratory tests**

Abrasion (min.0 to max. 4): **4**
Blade cut - coupe test (Index) (min.0 to Max. 5): **1**
Tear (min.0 to max. 4): **3**
Puncture (min.0 to max. 4): **1**
Cut resistance from sharp objects EN ISO
13997:1999 (min. 0 to Max. F, X - not tested): **A**
Impact protection (P if pass, F if failed): **-**

EN388:2016



4131A

**EN407:2004 Heat protection:
levels obtained in laboratory tests**

A - Burning behaviour: X of 4
B - Contact heat: 1 of 4
C - Convective heat: X of 4
D - Radiant heat: X of 4
E - Small drops molten metal: X of 4
F - Large quantity molten metal: X of 4

EN407:2004



X1XXXX

X = not tested or testing method is unsuitable for the design of the gloves.

EN420:2003+A1:2009 Dexterity (min.0 to max.5): **level 5.**

STORAGE AND SHELF LIFE

Please store the products in original packing in a dry and cool place without direct sunlight in general. The shelf life depends on the storage and other conditions. For the new product stored in a properly way, the shelf life of Xcellent 3005 can normally be 5 years.

CLEANING

Washing or dry-cleaning requires prior consultation with a recognized specialist, because such treatment may alter the protective properties of the glove. The gloves must always be checked for integrity before reuse. The rating with the marked performance levels based on tests on unused gloves.

WARNING

Don't use in case of chemicals, moving machines or electrical risk.
Please ensure the products are strictly used within their protection levels.

